

AHD-5936MW

Main Features

- 1.3M (1280x720 pixels) CMOS
- BNC interface, support for the general class of coaxial lossless transmission of up to 75-3 500 meters;
- High-speed, long-distance, real-time transmission; No delay;
- Support IR-CUT Switch, realize the day and night Monitor;
- Support 3D-DNR Noise Reduction,



Specification

Model	AHD-5936MW
Main Sensor	High-performance processor
Image sensor	1/4" CMOS image sensor
Effective Pixels	1080x720
Video Standard	AHD Standard
Video System	PAL / NTSC optional
Video Output	1CH AHD HD
Video Frame Rate	PAL : 1280x720@25fps NTSC : 1280x720@30fps
Transmission Max Distance	Common 75-3 coaxial cable transmission of more than 500 Metres
Day-Night	Support the IR - CUT Automatically Switch
Infrared Lamp	36 IR LED
IR Distance	20-25M
Lens	3.6 mm (Standard) / 6mm fixed lens
Mini Illumination	0.1 Lux (Color) / 0 Lux (Black) @ F1.2
Electronic Shutter	4/25s~1/45,000s
White Balance	Automatic / Manual
Backlight Compensation	Closed / Low / Middle / High / Higher
Strong Inhibition	Support
Color / Material	Milk white / Aluminum alloy
Working Voltage	DC12V 1A
Power Consumption	4W±10%
Work Environment	-20°C_55°C
Carton	18.5 Kg
Installation Environment	Indoor and Outdoor